

DATA SHEET

Battery Based Actuator Control System



The Concens C4 system is a versatile solution for control of electric actuators. The unique design, strong power supply system and the option of controlling multiple actuators makes the C4 system attractive for use in various applications.

The C4 system consists of:

- Control Box
- Handset
- Battery
- Battery charger

The C4 concept is designed for optimal flexibility making configuration, programming and installation very easy. Additionally, service and replacement of e.g. batteries are extremely easy with the patented magnetic principle. No tools are required.

The C4 Control Box is designed to handle up to four actuators in groups, synchronous or individually. It is controlled with a wired handset, which can be delivered in five different button layouts depending on customer needs. Furthermore, the C4 can be equipped with emergency stop.

The C4 system contains a rechargeable 24VDC NiMh or Li-Ion battery, enabling the actuator solution to be fully mobile.

Standard C4 solution includes IP50 protection with IP65 protection available.

Features

- 4-channel fully programmable controller
- Battery powered for mobile use
- 24VDC NiMh or Li-Ion replaceable battery
- Patented battery system
- Customized colors and foil design
- Wired handset
- Adjustable soft- start and stop
- Adjustable current limit in and out
- Adjustable calibration speed and current
- Adjustable virtual min/max-position
- Individual or synchronous operation for drive 2-3-4 or 2+2 actuator
- Audible and visual status signal

Technical Data

Supply 24VDC NiMH

or Li-Ion battery

Idle current < 5mA

Current limit 8A/ch max. total 12A

Current trip delay 30ms

Ramps 0-3 sec Operating temp. -20..70°C

Connector type Molex Mini-Fit 6 pin

Weight Control Box 430g

NiMH Battery Charger: 430g Li-Ion Battery Charger: 410g Battery: 530g (Li-lon: 400g)

Battery Capacity NiMH: 1400m Ah

Li-lon: 2100m Ah





System Components



C4 Control Box



C4 Brackets



Handsets



Customizable Foils



Battery Charger



Battery

Electrical Connections







- 1 Actuator 1
- 2 Actuator 2
- 3 Actuator 3
- 4 Actuator 4
- (5) Handset, External Power Emergency Stop



System Parameters




Mechanical Dimensions










C4 Item Number Combination









4

Please Note

- Concens does not have any responsibility over the possible errors in this data sheet
- Specifications subject to change without notice

Concens A/S
Øresundsvej 7
DK-6715 Esbjerg N
Denmark

T +45 70 11 11 31 F +45 76 10 50 10 E info@concens.com VAT DK10132266